

# DIN EN 853 2 SN SAE 100 R 2 S

Wire braid hydraulic hose meets EN 853 2SN, SAE 100R2 and ISO 1436 2SN



## GENERAL

<b>Tube</b>	Synthetic rubber, resistant against hydraulic fluids (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB, HFC)
<b>Reinforcement</b>	Two braids of high tensile steel wire
<b>Cover</b>	Abrasion and ozone resistant synthetic rubber Note: various covers available
<b>Temperature range</b>	-40°C to 100°C / -40°F to +212°F (max 120°C / 248°F intermittent)
<b>Standard branding</b>	Embossed tape

## TECHNICAL DETAILS

Nominal			Internal-Ø		Braid-Ø		External-Ø		Work. pressure (max.)		Min. burst pressure		Bending radius (min.)		Weight approx.	
mm	inch	dash	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	lbs/ft	kg/m
6	1/4	-4	6.6	0.26	12.4	0.49	14.3	0.56	400	5800	1600	23200	100	3.9	0.21	0.31
8	5/16	-5	8.3	0.33	14.0	0.55	16.0	0.63	350	5075	1400	20300	115	4.5	0.25	0.37
10	3/8	-6	9.9	0.39	16.4	0.65	18.4	0.72	330	4785	1320	19140	130	5.1	0.30	0.44
12	1/2	-8	13.0	0.51	19.4	0.76	21.3	0.84	275	4000	1100	16000	180	7.1	0.36	0.53
16	5/8	-10	16.4	0.65	22.6	0.89	24.6	0.97	250	3625	1000	14500	200	7.9	0.45	0.67
19	3/4	-12	19.5	0.77	26.6	1.05	28.6	1.13	215	3120	860	12480	240	9.4	0.56	0.84
25	1	-16	26.0	1.02	34.5	1.36	37.1	1.46	165	2395	660	9580	300	11.8	0.83	1.23
31	1-1/4	-20	32.5	1.28	43.9	1.73	46.7	1.84	125	1815	500	7260	420	16.5	1.20	1.79
38	1-1/2	-24	38.7	1.52	51.1	2.01	54.5	2.14	90	1305	360	5220	500	19.7	1.42	2.12
51	2	-32	51.1	2.01	62.9	2.47	66.7	2.63	80	1160	320	4640	630	24.8	1.88	2.79